



30

SAFETY ZONE DIMENSIONS (S)
Permanent speed limit 30mph or less
Sideways safety zone 0.5m
Longways safety zone 0.5m
(Dimensions are minima)

Drawing Office

<divDWG Number VH9011

Revision 0 Date Surveyed 12-11-25

Drawn By PT Date Drawn 12-11-25

Survey By PT Phase Number 9 of 10

Checked By GT Page Number 1 of 1



Site Details Address

Woodlands Avenue
leading
G5 3HJ
oad Closure/Diversion

- ot scale from this drawing, all dimensions to be verified on site.
- ll be the responsibility of the contractor to ensure that all temporary traffic management shall be in accordance with the Traffic Signs Manual chapter 8 2009, Safety at Street works 2013, Traffic Signs Regulations and General Directions 2016 and all current / relevant Health and safety legislation.
- ignage placement will be subject to available safe working space and all signage will be secured / ballasted with straps or sandbags.
- minimum lateral safety zone of 0.5M will be maintained at all times.
- minimum running lane of 3.0m will be maintained for buses and HGV's and a minimum of 2.5m for cars and light vehicles.
- afe segregated working area will be provided and maintained at all times.
- mum size of temporary signage will be 750mm.
- ck system to be utilised where practicable.
- minimum of 1.0m to be maintained for pedestrian access.

Drawing Notes
